



Ryvac Engineering Company

673 New York Drive, Pomona, CA 91768 U.S.A.

Tel: 818-241-7436 / Fax: 818-241-8712

www.ryvac.com

HEPA PNEUMATIC VACUUM

MODEL : RA-150-NLH

Features

- ✓ No moving parts for explosion proof applications
- ✓ Polyester fabric filter with manual shaker
- ✓ Easy dust bucket release and latch



Specifications

Maximum Air Flow:	105 CFM (3.0 M ₃ /min)
Maximum Vacuum:	100" H ₂ O (2500 mm)
Operating Input Air:	90-120 PSI
Air Consumption:	4.9 CFM@90 PSI
Air Line Connector:	3/8" FNPT
Air Hose:	3/8" I.D. 300PSI
1st Filter Area:	19 sq ft, Polyester
2nd Filter Area:	11 sq ft, HEPA
Dust Capacity:	15 Gallons
Noise Level:	75 dB A
Hose Inlet Diameter:	2" (50 mm)
Size W x L x H:	21" x 25" x 38"
Weight:	65 lbs

Filters

RV-00091-2, Polyester Duck, 12"L, 7 pcs (Standard)

RV-00091-4, One Micron Non-woven, 12"L, 7 pcs

RV-10675-5, HEPA, 11-1/2" Dia, 99.97%@.3 Micron

Performance Curve

